

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

DUPLICATE

FIELD NOTES

OF
THE DEPENDENT RESURVEY

OF

A PORTION OF THE EAST BOUNDARY

AND SUBDIVISIONAL LINES

AND THE

SUBDIVISION OF SECTIONS 22, 23, 24, 26, AND 27

IN

TOWNSHIP 36 SOUTH, RANGE 10 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Larry V. Judd
Cadastral Surveyor

Under special instructions dated *April 2, 1993*, approved April 2, 1993, which provided for the surveys included under Group Number 798, and assignment instructions dated *June 1, 1993*.

Survey commenced *April 25, 1994*

Survey completed *July 21, 1994*

INDEX DIAGRAM

Township 36 South , Range 10 West

6	5	4	3	2	1
7	8	9	10	11	12
				14	
18	17	16	15	14 14	13
			17 17	12 13	8
19	20	21	22	12 23	7 24 3
			16 17	10 11	5 6 2
30	29	28	16 27	9 26	4 25
			15 14	9	3
31	32	33	34	35	36

The Subdivision of Section 22.....	Page 18
The Subdivision of Section 23.....	Page 20
The Subdivision of Section 24.....	Page 23
The Subdivision of Section 26.....	Page 25
The Subdivision of Section 27.....	Page 28

TOWNSHIP 36 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary and subdivisional lines and the subdivision of sections 22, 23, 24, 26, and 27, in Township 36 South, Range 10 West, Salt Lake Meridian, Utah.

History of Surveys**Surveyed by****Retr. or Resurveyed by****NORTH BOUNDARY (Seventh Standard Parallel South)**

All	A.J. Stewart	1873		
All			J.H. Martineau	1881
All			M.H. Dalley	1908

SOUTH BOUNDARY

All	A.J. Stewart	1873		
All			J.H. Martineau	1881
Portion			H.W. Miller	1929

EAST BOUNDARY

All	J.H. Martineau	1881		
All			Jenkins and West	1897
Portion			M.H. Dalley	1907
Portion			Bird and Nelson	1924

WEST BOUNDARY

Portion	A.J. Stewart	1874		
All	J.H. Martineau	1881	J.H. Martineau	1881
Portion			L.A. Snow	1908

SUBDIVISION

All	J.H. Martineau	1881		
Portion			G.E. Reynolds	1986

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 798, Utah, dated April 2, 1993.

The directions of lines were determined by references to true meridians established on line by hour angle observations of the sun and Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

TOWNSHIP 36 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 25, 26, 35, and 36, as determined by a tie made to the corner of sections 16, 17, 20, and 21, a B.L.M. Control Station is as follows:

Latitude $37^{\circ} 38' 06.57''$ N. Longitude $112^{\circ} 56' 29.06''$ W.
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1990" is: $13 \frac{1}{2}^{\circ}$ East.

Dependent Resurvey of a Portion of the East Boundary,
T. 36 S., R. 10 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J.H. Martineau, Deputy Surveyor in 1881, and the Resurveys
by W. Jenkins and J. West in 1897 and M.H. Dalley in 1907

Beginning at the corner of sections 24 and 25 only, on the east boundary of the township, monumented with a lava stone, 20x12x4 ins., firmly set and plainly marked with 2 notches on the S edge and 4 grooves on the N edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T36S	
R10W R9W	
S24	
S25	
1994	

Buried the marked rock alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 3 ft. high, west of the corner.

The corner falls on flat ground, at the edge of a grove of aspen trees, 55 lks. north of a trail road, 15 lks. wide, bears N. 70° W. and S. 70° E., and 9 lks. east of a net wire fence, bears north and south.

N. $0^{\circ} 16.2'$ E., along the east boundary of section 24.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over high rolling mountainous land.

43.030

The 1/4 section corner of section 24 only, monumented with a lava stone, 18x10x6 ins., firmly set, plainly marked 1/4 on the W face, with a scattered mound of stone to the west.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, set in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T36S
R10W R9W
1/4 |
S24 |
1994

Buried the marked rock alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 3 ft. high, west of the corner.

The corner falls on flat ground in a large clearing, 41 lks. W of a net wire fence, projecting north and south and 1.40 chs. S of the south edge of a pond, 70 lks. wide by 1.65 chs. long.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 36 S., R. 10 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J.H. Martineau, Deputy Surveyor in 1881

From the corner of sections 25, 26, 35, and 36, monumented with a white sandstone, 18x12x6 ins., firmly set, plainly marked with 1 groove on the S and 1 groove on the E edges, with an X chiseled on the top of the rock.

From which:

A cedar, 18 ins. in diam., bears N. 68° E., 80 lks. dist., with no visible scribe marks on open blaze.

A cedar, 18 ins. diam., bears N. 30° W., 13 lks. dist., laying over on a very steep slope with illegible scribes visible.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

This corner was set by M.H. Dalley, Land Surveyor for Iron County, Utah, in a survey executed for Uriah T. Jones and William T. Jones in October of 1894. Typewritten notes of this survey were obtained from Stephen R. Platt, of Platt and Platt Engineering, present Iron County Surveyors.

This corner has been accepted and utilized by local land owners and private land surveyors as the position for the corner of sections 25, 26, 35, and 36, and is accepted as the section corner position. No remaining evidence of the original corner set by J.H. Martineau, U.S. Deputy Surveyor in 1881 was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with aluminum cap marked:

T36S R10W	
S26	S25
S35	S36
1994	

Buried the marked rock alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 3 ft. high, west of the corner.

The corner falls on steep broken westerly slope.

N. 1°29.6' E., between sections 25 and 26.

Ascending over steep westerly slope.

19.451 Point for the S 1/16 section corner of sections 25 and 26; not monumented.

38.902 Point for the 1/4 section corner of sections 25 and 26, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W	
1/4	
S26	S25
1994	

From which

A fir, 16 ins. diam., bears N. 24° E., 33 lks. dist., marked
T36S R10W S25 BT

Raise a mound of stone, 3 ft. base, 1 ft. high, west of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS
58.353

Point for the N 1/16 section corner of sections 25 and 26.

Raise a mound of stone, 4 ft. base, 2 ft. high, west of the corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap marked:

T36S R10W
N 1/16
S26 | S25
1994

The corner falls on a steep northwest slope.

66.20 Last Chance Wash, drains SW.

67.70 Dirt road, 20 lks. wide, bears N. 71° E. and S. 71° W.

71.90 Same dirt road, bears E. and W.

77.804 The corner of sections 23, 24, 25, and 26, monumented with a sandstone, 23x15x4 ins., firmly set in the ground within a rotted out tree stump, 16 ins. diam., plainly marked with 3 notches on the S and 2 notches on the E edges. (Record, marked a pinon pine tree, 9 ins. diam., with 2 notches on the S and 1 notch on the E edges, for the corner.)

from which

A pinon pine, 20 ins. diam., laying dead on the ground, with blazed face, with 2 hack marks and scribes visible, bears N. 62° E., 43 lks. dist., (Record N. 66° E., 49 lks. dist.)

A pinon pine, 20 ins. diam., laying dead on the ground, with blazed face, with 2 hack marks and no visible scribe marks, bears S. 80° W., 27 lks. dist.

A pinon pine stump, 12 ins. diam., with remainder of tree laying alongside with 2 hack marks and no scribe marks bears N. 74° W., 10 lks. dist.

A juniper, 16 ins. diam., blazed face with no scribe marks, bears N. 82° E., 14 lks. dist. (There is no record of this tree being marked.)

No remaining evidence of the SE bearing tree could be found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T36SR10W
 $\frac{S23}{S26} \mid \frac{S24}{S25}$
 1994

Buried the marked rock alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 2 ft. high, north of the corner.

The corner falls on flat ground, 20 lks. W of a steep decent.

From the corner of sections 24 and 25 only, on the east boundary of the township, hereinbefore described.

N. 89°09.0' W., between sections 24 and 25.

Over steep southwesterly slope.

20.940 Point for the E 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
 E 1/16 $\frac{S24}{S25}$
 1994

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

The corner falls on a moderate W slope, 23 lks. N of a net wire fence, projecting east and west.

35.880 Point selected for the witness corner to the 1/4 section corner of sections 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, set in a mound of stone, 3 ft. base to top of aluminum cap marked:

T36S R10W
 WC
 1/4 $\leftarrow \frac{S24}{S25}$
 1994

The corner falls on a steep NW slope.

36.63 Top edge of vertical ledge 25 ft. high, bears N. 11° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

41.880

Point for the 1/4 section corner of sections 24 and 25, at proportionate distance. The point falls on a steep unstable slope of red sandstone breaks, not suitable for permanent monumentation.

No remaining evidence of the original corner was found.

62.820

Point for the W 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, set in a mound of stone, 3 ft. base to top of aluminum cap marked:

T36S R10W
W 1/16 $\frac{S24}{S25}$
1994

The corner falls on a steep SW slope of white sandstone breaks.

83.760

The corner of sections 23, 24, 25, and 26.

N. 0°04.5' E., between sections 23 and 24.

Ascending on southerly slope.

17.73

Netwire fence bears E and W.

19.728

Point for the S 1/16 section corner of sections 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
S 1/16
S23 | S24
1994

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

The corner falls on flat ground in scattered juniper, pinon and mahogany.

39.456

The 1/4 section corner of sections 23 and 24, monumented with a sandstone, 18x8x4 ins., firmly set, plainly marked 1/4 on the W face

from which

A ponderosa pine, 40 ins. diam., bears N. 85°43' W., 0.995 chs. dist.
(Record, West 1.02 chs. dist.), with visible scribe and hack marks
on partially open blaze.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
1/4
S23 | S24
1994

from which a new bearing tree

A pinon pine, 16 ins. diam., bears N. 15° E., 31 lks. dist., marked
1/4 S 24 BT.

Buried the marked rock alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

The corner falls on a gradual easterly slope.

N. 0°02.5 E., beginning new measurement.

19.762 Point for the N 1/16 section corner of sections 23 and 24; not monumented.

39.524 The corner of sections 13, 14, 23, and 24, monumented with a sandstone, 14x8x6 ins., laying loose, dimly marked with 2 grooves on the S and 1 groove on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
S14 | S13
S23 | S24
1994

from which

A fir, 14 ins. diam., bears S. 22° E., 22 lks. dist., marked
T36S R10W S24 BT.

A fir, 6 ins. diam., bears S. 62° W., 24 lks. dist., marked X BT.

Buried the marked rock alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 2 ft. high, north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner falls on a steep NW slope in oak brush undergrowth with scattered fir trees.

From the corner of sections 25, 26, 35, and 36.

S. 88°53.5' W., between sections 26 and 35.

Descend into Coal Creek.

5.60 Center of Coal Creek, drains N. 40° W.

17.43 Center line of State Highway No. 14, bears N. 55° W. and S. 55° E.

18.779 Point for the E 1/16 section corner of sections 26 and 35; not monumented.

37.558 The 1/4 section corner of sections 26 and 35, monumented with a sandstone, 18x10x8 ins., firmly set, plainly marked 1/4 on the N face, with mound of stone, 3 ft. base by 1 ft. high, S of the corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T36S R10W
1/4	<u>S26</u>
	S35
	1994

Buried the marked rock alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

The corner falls on a moderate NE slope in oak brush and scattered juniper, 20 lks. W of steep descent over northeasterly slope.

From the 1/4 section corner of sections 26 and 27, monumented with a white sandstone, 12x11x6 ins., firmly set, plainly marked 1/4 on the W face set in a mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T36S R10W
	1/4
S27	S26
	1994

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Buried the marked rock alongside the aluminum post.

Raise a mound of stone, 5 ft. base, 3 ft. high, north on the downhill side.

The corner falls on a moderate N slope, in oak brush undergrowth and scattered fir.

N. 1°01.5' W., between sections 26 and 27.

Descending into Coal Creek.

5.35 Center of Coal Creek, drains N. 22° W.

7.65 Center line of State Highway No. 14, bears N. 89° W. and S. 89° E.

36.173 The corner of sections 22, 23, 26, and 27, monumented with a sandstone 18x16x10 ins., firmly set, plainly marked with 2 grooves on the S, and 2 grooves on the E edges, set in a small mound of stone.

from which

A juniper, 18 ins. diam., with visible blaze and axe marks, no scribe marks, bears N. 37° E., 97 lks. dist. (Record, N. 10° E., 70 lks. dist.).

A pinon pine, 16 ins. diam., with visible blaze and axe marks, no scribe marks, bears S. 57° E., 44 1/2 lks. dist. (Record, S. 40° E., 32 lks. dist.)

A pinon pine, 16 ins. diam., with visible blaze and axe marks, no scribe marks, bears S. 40° W., 26 lks. dist. (Record, S. 15° W., 12 lks. dist.)

No remaining evidence of the NW bearing tree was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

T36S R10W	
S22	S23
S27	S26
1994	

Placed the marked rock within the mound.

The corner falls on top of ridge on a steep SW slope.

From the corner of sections 23, 24, 25, and 26.

S. 88°18.0' W., between sections 23 and 26.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling southerly slope.

20.215 Point for the E 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
E 1/16 $\frac{S23}{S26}$
1994

Raise a mound of stone, 4 ft. base, 2 ft. high, north of the corner.

The corner falls on a steep easterly slope in scattered pinon and juniper.

40.430 Point for the 1/4 section corner of sections 23 and 26, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
1/4 $\frac{S23}{S26}$
1994

Raise a mound of stone, 4 ft. base, 2 ft. high, north of the corner.

The corner falls on a gradual southerly slope in scattered pinon and juniper.

60.645 Point for the W 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
W 1/16 $\frac{S23}{S26}$
1994

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

The corner falls on moderate SE slope.

80.860 The corner of sections 22, 23, 26, and 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. $0^{\circ}21.0'$ E., between sections 22 and 23.

Ascending on southeasterly slope.

40.080

Point for the $1/4$ section corner of sections 22 and 23, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with aluminum cap marked:

T36S R10W
1/4
S22 | S23
1994

Raise a mound of stone, 3 ft. base, 3 ft. high, west of the corner.

The corner falls on a moderate westerly slope, 1.30 chs. W of the top of ridge, bears N and S in dense oak brush undergrowth and scattered pinon.

60.120

Point for the N $1/16$ section corner of sections 22 and 23.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
N $1/16$
S22 | S23
1994

Raise a mound of stone, 4 ft. base, 2 ft. high, west of the corner.

The corner falls on a steep northerly slope.

60.47

Center of Pickering Creek, 4 lks. wide, drains N. 58° W.

70.81

Center of creek in bottom of Maple Canyon, 5 lks. wide, drains S. 10° W.

80.160

Point for the corner of sections 14, 15, 22, and 23, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., alongside a partially exposed boulder on solid rock, set in a mound of stone, 5 ft. base to top of aluminum cap marked:

T36S R10W
S15 | S14
S22 | S23
1994

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner falls on a steep easterly slope, 60 lks. E., of the top of a finger ridge, 20 lks. wide, bears N. 22° W.

From the corner of sections 13, 14, 23, and 24.

S. 89°07.7' W., between sections 14 and 23.

Along steep northwesterly slope.

20.103 Point for the E 1/16 section corner of sections 14 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
E 1/16 $\frac{S14}{S23}$
1994

Raise a mound of stone, 3 ft. base, 3 ft. high, north of the corner.

The corner falls near the bottom of Pickering Creek on a moderate westerly slope.

21.35 Bottom of Pickering Creek, 5 lks. wide, drains S. 35° W.

40.206 The 1/4 section corner of sections 14 and 23 at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
1/4 $\frac{S14}{S23}$
1994

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

The corner falls on the top of a ridge, 2 chs. wide, which bears N. 55° E. and S. 55° W.

73.90 Center of creek in bottom of Maple Canyon, 4 lks. wide, drains S. 10° E.

80.412 The corner of sections 14, 15, 22, and 23.

N. 0°11.0' W., between sections 14 and 15.

Over broken mountainous terrain.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS
40.077

Point for the 1/4 section corner of sections 14 and 15 at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
1/4
S15 | S14
1994

Raise a mound of stone, 4 ft. base, 2 ft. high, west of the corner.

The corner falls on the S edge of an old slide area on a steep westerly open slope.

41.08

Flat Bench area covered with sagebrush undergrowth.

80.154

The corner of sections 10, 11, 14, and 15, monumented with a broken lava stone, laying loose, dimly marked with 3 grooves visible on the S and 2 grooves on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, set in a mound of stone, 5 ft. base to top of aluminum cap marked:

T36S R10W
S10 | S11
S15 | S14
1994

The corner falls on a gradual south rocky slope on point of a ridge projecting north and south, in dense oak brush undergrowth and scattered pinon and juniper.

From the 1/4 section corner of sections 27 and 34, monumented with a sandstone, 16x10x8 ins., firmly set in a mound of stone, with 1/4 plainly marked on the N face, and a steel fence post set north of the rock. This corner was marked and set by Ralph B. Platt of Platt and Platt Engineering (date unknown), based on proportionate measurement. This corner is accepted after verification of a tie to the corner of sections 26, 27, 34, and 35. No remaining evidence of the original corner was found.

At the corner point

Set a rebar 3/4 in. diam., 6 ins. long, drilled 4 ins. into solid rock, with 3 in. diam., aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T36S R10W

1/4 $\frac{S27}{S34}$
1994

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

From this corner, the corner of sections 26, 27, 34, and 35, monumented with an Iron County 2 1/2 in. diam., iron post, firmly set, projecting 3 ins. above ground with a sandstone, 19x10x7 ins. marked with 2 grooves on the E and 1 groove on the S edges, found alongside the iron post, bears N. 87°27.6' E., 41.142 chs., with brass cap marked, IRON COUNTY T 36 S R 10 W S26 S27 S34 S35 1994 SURVEY MONUMENT.

S. 87°25.0' W., between sections 27 and 34.

Over rolling northerly slope through dense oak brush undergrowth.

20.571 Point for the W 1/16 section corner of sections 27 and 34; not monumented.

41.142 The corner of sections 27, 28, 33, and 34, monumented with an Iron County 2 1/2 in. diam., iron post, firmly set in a mound of stone 5 ft. base to top of brass cap, with a sandstone 20x10x6 ins. marked with 3 notches on the E and 1 notch on the S edges found alongside the iron post, with brass cap marked, IRON COUNTY T36S R10W S27 S28 S33 S34 1989 L.S. 4501.

The corner falls on a steep E slope, in dense oakbrush undergrowth.

N. 0°30.0' E., between sections 27 and 28.

Over top of Cedar Mountain, through dense oak brush undergrowth.

19.518 Point for the S 1/16 section corner of sections 27 and 28, monumented with a rebar 5/8 in. diam., firmly set, with a 1 in. diam., yellow plastic cap marked, ADAMS SURVEYING L.S. No. 6904.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
S 1/16
S28 | S27
1994

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, west of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the found rebar and cap inside the aluminum post.

The corner falls on a gradual westerly slope, in oak brush undergrowth.

39.036

Point for the 1/4 section corner of sections 27 and 28, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with a 1 in. diam., yellow plastic cap marked ADAMS SURVEYING L.S. 6904. This corner is accepted as a careful and faithful perpetuation of the position of the original corner.

No remaining evidence of the original corner was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

T36S R10W
1/4
S28 | S27
1994

Deposit the found rebar and cap inside the aluminum post.

The corner falls on a very steep N slope, in oak brush undergrowth.

58.554

Point for the N 1/16 section corner of sections 27 and 28; not monumented

78.072

The corner of sections 21, 22, 27, and 28, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, found 6 ins. below ground, with a mound of stone, 5 ft. base by 3 ft. high, north of the corner, with aluminum cap marked as described in the official record of the resurvey by G.E. Reynolds in 1986.

From this corner, the corner of sections 16, 17, 20, and 21, a B.L.M. Control Station monumented with a 2 1/2 in. diam., aluminum post, firmly set projecting 4 ins. above a mound of stone, with aluminum cap marked as described in the official record of the resurvey executed by Gail E. Reynolds in 1986, bears N. 44°13.5' W., 113.716 chs. distance.

From the corner of sections 22, 23, 26, and 27.

S. 88°38.6' W., between sections 22 and 27.

Over southerly mountainous slope.

40.072

Point for the 1/4 section corner of sections 22 and 27, at proportionate distance. No remaining evidence of the original corner was found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
1/4 $\frac{S22}{S27}$
1994

Raise a mound of stone, 4 ft. base, 3 ft. high, north of the corner.

The corner falls alongside a boulder, 12x12x6 ft. above ground on a steep SW slope.

40.55 Drainage, 20 lks. wide, drains NW.

60.108 Point for the W 1/16 section corner of sections 22 and 27; not monumented.

80.144 The corner of sections 21, 22, 27, and 28.

From the corner of sections 14, 15, 22, and 23.

S. 89°49.0' W., between sections 15 and 22.

On steep southerly slope.

40.322 Point for the 1/4 section corner of sections 15 and 22, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., at the base of ledges on solid rock, set in a mound of stone, 5 ft. base to top of aluminum cap marked:

T36S R10W
1/4 $\frac{S15}{S22}$
1994

The corner falls on a moderate SE slope in scattered pinon and juniper.

80.644 The corner of sections 15, 16, 21, and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with a mound a stone W, and a cedar post alongside the corner, with aluminum cap marked as described in the official record of the resurvey executed by G.E. Reynolds in 1986.

THE SUBDIVISION OF SECTION 22,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 22,
T. 36 S., R. 10 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 22 and 27.

N. 0°09.3' E., on the N - S center line of section 22.

20.612 Point for the center S 1/16 section corner of section 22; not monumented

40.60 Drainage, 5 lks. wide at the bottom, drains S. 80° E.

41.224 Point for the center 1/4 section corner, at intersection with the E - W center line of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
C 1/4
S22
1994

The corner falls on a steep SE slope.

60.996 Point selected for the witness corner to the center N 1/16 section corner of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins in the ground to bedrock, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

T36S R10W
WC
C
N 1/16 ↑ S22
C
1994

The corner falls on a steep SE slope.

61.099 True point for the center N 1/16 of section 22, falls on sandstone outcrop 12x12 ft.; not monumented.

80.974 The 1/4 section corner of sections 15 and 22.

From the 1/4 section corner of sections 22 and 23.

N. 89°43.0' W., on the E - W center line of section 22.

40.190 The center 1/4 section corner of section 22.

THE SUBDIVISION OF SECTION 22,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS**59.060**

Point selected for the witness corner to the center W 1/16 section corner of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
WC
C ← W 1/16 → C
S22
1994

Raise a mound of stone, 4 ft. base, 3 ft. high, west of the corner.

The corner falls at the base of a 4 ft. high ledge on a steep westerly slope, on the easterly edge of a drainage, 20 lks. E of the bottom, drains S. 72° W.

60.190

True point for the center W 1/16 section corner falls on a steep SW slope at the base of unstable ledges; not monumented

80.190

The 1/4 section corner of sections 21 and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base to top of aluminum cap marked as described in the official record of the resurvey by G.E. Reynolds in 1986.

From the N 1/16 section corner of sections 22 and 23.

N. 89°57.0' W., on the E - W center line of the NE 1/4 of section 22.

40.256

The center N 1/16 section corner of section 22.

From the point for the W 1/16 section corner of sections 22 and 27.

N. 0°11.5' E., on the N - S center line of the SW 1/4 of section 22.

20.896

Point for the SW 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
SW 1/16
S22
1994

Raise a mound of stone, 4 ft. base, 3 ft. high, west of the corner.

THE SUBDIVISION OF SECTION 22,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner falls on a steep S slope, in scattered pinon and juniper.

41.798 Point for the center W 1/16 section corner of section 22.

From the center S 1/16 section corner of section 22.

S. 89°27.3' W., on the E - W center line of the SW 1/4 of section 22.

20.016 The SW 1/16 section corner of section 22.

40.032 The S 1/16 section corner of sections 21 and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set in the ground, with a mound of stone, 4 ft. base by 3 ft. high, built up on the S side of the post, with aluminum cap marked as described in the official record of the resurvey by G.E. Reynolds in 1986.

The Subdivision of Section 23,
T. 36 S., R. 10 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 23 and 26.

N. 0°12.3' E., on the N - S center line of section 23.

19.883 Point for the center S 1/16 section corner of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
C
S 1/16 | S23
C
1994

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

The corner falls 5 lks. S of the south edge of a dirt road, 15 lks. wide, bears N. 74° W. and S. 74° E.

39.766 Point for the center 1/4 section corner at intersection with the E - W center line of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 23,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T36S R10W

C 1/4

S23

1994

The corner falls on a moderate W slope in dense oak brush undergrowth.

59.666 Point for the center N 1/16 section corner of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W

C

N 1/16 | S23

C

1994

Raise a mound of stone, 2 ft. base, 2 ft. high, west of the corner.

The corner falls on a gradual SE slope in dense oak brush undergrowth.

79.566 The 1/4 section corner of sections 22 and 23.

From the 1/4 section corner of sections 23 and 24.

S. 88°44.3' W., on the E - W center line of section 23.

20.164 Point for the center E 1/16 section corner of section 23; not monumented

40.328 The center 1/4 section corner of section 23.

60.486 Point for the center W 1/16 section corner of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

T36S R10W

C W 1/16 C

S23

1994

The corner falls on a steep N slope, approximately 2 chs. south of the bottom of Pickering Creek.

80.644 The 1/4 section corner of sections 22 and 23.

THE SUBDIVISION OF SECTION 23,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- From the point for the center E 1/16 section corner of section 23.
- N. 0°07.4' E., on the N - S center line of the NE 1/4 of section 23.
- 19.831** Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 23.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap marked:
- T36S R10W
NE 1/16
S23
1994
- Raise a mound of stone 4 ft. base, 3 ft. high, west of the corner.
- The corner falls on a moderate W slope, in dense oak brush undergrowth in scattered pinon, mahogany and juniper.
- 39.662** The E 1/16 section corner of sections 14 and 23.
-
- From the point for the N 1/16 section corner of sections 23 and 24.
- S. 88°56.0' W., on the E - W center line of the NE 1/4 of section 23.
- 20.133** The NE 1/16 section corner of section 23.
- 24.55** Dirt road, 15 lks. wide, bears NE and S. 28° W.
- 40.266** The center N 1/16 section corner of section 23.
-
- From the S 1/16 section corner of sections 23 and 24.
- S. 88°31.2' W., on the E - W center line of the SE 1/4 of section 23.
- 40.379** The center S 1/16 section corner of section 23.
-
- From the W 1/16 section corner of sections 23 and 26.
- N. 0°16.6' E., on the N - S center line of the SW 1/4 of section 23.
- 39.922** The center W 1/16 section corner of section 23.
-

THE SUBDIVISION OF SECTION 24,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 24,
T. 36 S., R. 10 W., Salt Lake Meridian, Utah

From the true point for the 1/4 section corner of sections 24 and 25.

N. 1°16.5' W., on the N - S center line of section 24.

20.612 Point for the center S 1/16 section corner; not monumented

41.224 Point for the center 1/4 section corner at intersection with the E - W center line of section 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

T36S R10W
C 1/4
S24
1994

from which

A ponderosa pine, 18 ins. diam., bears S. 78° E., 25 1/2 lks. dist.,
marked T36S R10W C 1/4 S24 BT

The corner falls on a gradual NW slope in red sandstone breaks.

80.148 The 1/4 section corner of sections 13 and 24, monumented with a limestone, 15x10x8 ins., firmly set, dimly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

T36S R10W
1/4 S13
S24
1994

Buried the marked rock alongside the aluminum post.

The corner falls on a moderate S slope in dense oak brush and scattered juniper, 95 lks. N of a trail road, 15 lks. wide, bears NE and SW.

THE SUBDIVISION OF SECTION 24,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of section 24 only on the east boundary of the township, hereinbefore described.

S. 88°24.5' W., on the E - W center line of section 24.

21.504 Point for the center E 1/16 section corner of section 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone, 3 ft. base to top of aluminum cap marked:

T36S R10W
C $\frac{E \ 1/16}{S24}$ C
1994

The corner falls on a steep open SW slope, in red sandstone breaks.

43.008 The center 1/4 section corner of section 24.

63.467 Point for the center W 1/16 section corner of section 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

T36S R10W
C $\frac{W \ 1/16}{S24}$ C
1994

The corner falls on a gradual SW slope on top of ridge, in dense oak brush undergrowth.

64.45 Net wire fence, bears N and S.

83.926 The 1/4 section corner of sections 23 and 24.

From the E 1/16 section corner of sections 24 and 25.

N. 0°29.2' W., on the N - S center line of the SE 1/4 of section 24.

42.122 The center E 1/16 section corner of section 24.

From the W 1/16 section corner of sections 24 and 25.

N. 0°37.0' W., on the N - S center line of the SW 1/4 of section 24.

18.67 Bottom of drainage, 25 lks. wide, drains S. 47° W.

THE SUBDIVISION OF SECTION 24,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS**20.168**

Point for the SW 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T36S R10W
SW 1/16
S24
1994

Raise a mound of stone, 4 ft. base, 2 ft. high, west of the corner.

The corner falls on a gradual S slope, in scattered fir and pinon.

40.336

The center W 1/16 section corner of section 24.

From the point for the center S 1/16 section corner of section 24.

S 89°38.5' W., on the E - W center line of the SW 1/4 of section 24.

19.20

Drainage, 25 lks. wide, drains S. 42° W.

19.70

Drainage, 18 lks. wide, drains S. 10° W.

20.695

The SW 1/16 section corner of section 24.

41.390

The S 1/16 section corner of sections 23 and 24.

The Subdivision of Section 26,
T. 36 S., R. 10 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 26 and 35.

N. 0°37.5' W., on the N - S center line of section 26.

15.84

Center line of State Highway No. 14, bears N. 35° W. and S. 35° E.

18.489

Point selected for the witness corner to the center S 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 26,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T36S R10W
WC
C
S 1/16 ↑ S26
C
1994

Raise a mound of stone, 5 ft. base, 2 ft. high, west of the corner.

The corner falls on a bench above Coal Creek, 1.80 chs. S of the center of Coal Creek, 20 lks. wide, drains N. 85° W.

19.889 True point for the center S 1/16 section corner of section 26, falls near Coal creek, unsuitable for permanent monumentation; not monumented

39.778 Point for the center 1/4 section corner at intersection with the E- W center line of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
C 1/4
S26
1994

The corner falls on a steep westerly slope.

43.85 Center of dirt road, 20 lks. wide, bears N. 83° E. and S. 83° W.

58.545 Point for the center N 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, set in a mound of stone, 6 ft. base to top of aluminum cap marked:

T36S R10W
C
N 1/16 | S26
C
1994

The corner falls on a steep SW slope.

77.312 The 1/4 section corner of sections 23 and 26.

From the 1/4 section corner of sections 25 and 26.

N. 89°46.0' W., on the E - W center line of section 26.

THE SUBDIVISION OF SECTION 26,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

19.497

Point for the center E 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
C E 1/16 C
S26
1994

The corner falls on a steep westerly slope in dense oak brush undergrowth.

38.994

The center 1/4 section corner of section 26.

40.82

Dirt road, 20 lks. wide, bears N. 83° E. and S. 64° W.

79.173

The 1/4 section corner of sections 26 and 27.

From the center E 1/16 section corner of section 26.

N. 0°27.2' E., on the N - S center line of the NE 1/4 of section 26.

15.78

Dirt road, 20 lks. wide, bears N. 40° E. and S. 40° W.

19.106

Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, set in a mound of stone, 6 ft. base to top of aluminum cap marked:

T36S R10W
NE 1/16
S26
1994

The corner falls on a steep S slope.

38.212

The E 1/16 section corner of sections 23 and 26.

From the N 1/16 section corner of sections 25 and 26.

S. 89°15.0' W., on the E - W center line of the NE 1/4 of section 26.

13.95

Dirt road, 20 lks. wide, bears NE and SW.

19.853

The NE 1/16 section corner of section 26.

THE SUBDIVISION OF SECTION 26,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.706

The center N 1/16 section corner of section 26.

From the point for the E 1/16 section corner of sections 26 and 35.

N. 0°25.3' E., on the N - S center line of the SE 1/4 of section 26.

19.667

Point for the SE 1/16 section corner at intersection with the E - W center line of the SE 1/4 of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, set in a mound of stone, 7 ft. base to top of aluminum cap marked:

T36S R10W
SE 1/16
S26
1994

The corner falls on a steep SW slope.

39.334

The center E 1/16 section corner of section 26.

From the point for the S 1/16 section corner of sections 25 and 26.

S. 89°34.5' W., on the E - W center line of the SE 1/4 of section 26.

19.137

The SE 1/16 section corner of section 26.

38.274

True point for the center S 1/16 section corner of section 26.

The Subdivision of Section 27,
T. 36 S., R. 10 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 27 and 34.

N. 0°15.7' W., on the N - S center line of section 27.

19.782

Point for the center S 1/16 section corner of section 27; not monumented

35.45

Bottom of Ellis Canyon, drains N. 30° E.

39.564

Point for the center 1/4 section corner at intersection with the E - W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 27,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T36S R10W

C 1/4

S27

1994

The corner falls on a steep easterly slope, in dense oak brush undergrowth.

58.364 Point for the center N 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., over the top of a steel fence post, 5 1/2 ft. long, driven 5 1/2 ft. into the ground with aluminum cap marked:

T36S R10W

C

N 1/16 | S27

C

1994

The corner falls in an old slide area, on a steep NE slope.

59.50 Center of Coal Creek, 20 lks. wide, drains NW.

60.95 Center of Coal Creek, 30 lks. wide, drains NW from the SW.

65.47 Center of State Highway No. 14, bears NW and SE.

77.164 The 1/4 section corner of sections 22 and 27.

From the 1/4 section corner of sections 26 and 27.

S. 86°38.4' W., on the E - W center line of section 27.

40.610 The center 1/4 section corner of section 27.

60.933 Point for the center W 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W

C $\frac{W \ 1/16}{S27}$ C

S27

1994

The corner falls on flat ground, on the edge of a clearing in dense oak brush undergrowth.

81.256 The 1/4 section corner of sections 27 and 28.

THE SUBDIVISION OF SECTION 27,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the W 1/16 section corner of sections 27 and 34.

N. 0°07.1' E., on the N - S center line of the SW 1/4 of section 27.

19.650 Point for the SW 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T36S R10W
SW 1/16
S27
1994

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, west of the corner.

The corner falls on a finger ridge, 75 lks. S, of a drainage, 20 lks. wide, drains N. 60° E.

39.300 The center W 1/16 section corner of section 27.

From the point for the center S 1/16 section corner of section 27.

S. 87°01.8' W., on the E - W center line of the SW 1/4 of section 27.

20.447 The SW 1/16 section corner.

40.894 The S 1/16 section corner of sections 27 and 28.

From the center W 1/16 section corner of section 27.

N. 0°07.6' E., on the N - S center line of the NW 1/4 of section 27.

19.159 Point for the NW 1/16 section corner at intersection with the E - W center line of the NW 1/4 of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, set in a mound of stone, 4 ft. base to top of aluminum cap marked:

T36S R10W
NW 1/16
S27
1994

THE SUBDIVISION OF SECTION 27,
T. 36 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner falls on a gradual NE slope in dense oak brush undergrowth.

38.318

Point for the W 1/16 section corner of sections 22 and 27.

From the center N 1/16 section corner of section 27.

S. 87°38.1' W., on the E - W center line of the NW 1/4 of section 27.

20.177

The NW 1/16 section corner of section 27.

40.354

Point for the N 1/16 section corner of sections 27 and 28.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Shane Button	Survey Aid

CERTIFICATE OF SURVEY

I, **Larry V. Judd, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *2nd day of April, 1993*, I have *dependently resurveyed a portion of the east boundary and subdivisional lines and subdivided sections 22, 23, 24, 26, and 27, in Township 36 South, Range 10 West,*

of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 4, 1997

Date

/s/ Larry V. Judd

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the east boundary and subdivisional lines and the subdivision of sections 22, 23, 24, 26, and 27, in Township 36 South, Range 10 West, Salt Lake Meridian, Utah,*

executed by *Larry V. Judd, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

March 18, 1998

Date

/s/ Daniel W. Webb

(Chief Cadastral Surveyor for Utah)

CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above-described surveys in *T. 36 S., R. 10 W., Salt Lake Meridian, Utah*, is a true copy of the original field notes.

March 18, 1998

Date

Daniel W. Webb

(Authorizing Signature)